

Cone connector Cu

■ FRL 4 Cone connecto



Application

For copper wire

Characteristics

The cone connector locks automatically. By installing the wire in the sleeve a reliable connection will be established. When ordering, please indicate the conductor construction, diameter and number of single wires.

Before installing, the cut wire must be chamfered.

Legend

a) Conical coupling

| Article-Nr. | E-Number | | | | | | | | | |
|-------------|-------------|----|--|-------|--|--|--|--|----|----|
| 125.071.002 | 156 040 090 | Cu | | 6 - 4 | | | | | a) | 10 |

Technical Specifications: **Cone connecto FRL 4**

| | |
|--------------------------------|----------------------|
| Article No. | 125.071.002 |
| Wire diameter | 6 - 4 mm |
| Suitable for solid cores | Yes |
| Useful for stranded conductors | No |
| Nominal cross section | 29 mm ² |
| Material | Cu |
| Sleeve form | Long |
| For pull protected connections | Yes |
| Suitable for round conductors | Yes |
| Voltage level | Up to 35kV |
| Model | Standard version |
| Number of branches | 2 |
| Surface protection | blank |
| Oil stop/centre bar | No |
| Type of connection | Percussion connector |
| comment | a) |
| Commercial specification | |
| Customs number | 85389000 |
| country of origin | CH |
| Texte | |
| comment | a) |
| Logistic specification | |
| VPE Weight | 1.298 kg |

