

## Cone connector Cu

### ■ FRL 4 Cone connecto



#### Application

For copper wire






#### Characteristics

The cone connector locks automatically. By installing the wire in the sleeve a reliable connection will be established. When ordering, please indicate the conductor construction, diameter and number of single wires.

Before installing, the cut wire must be chamfered.

#### Legend

a) Conical coupling

| Article-Nr. | E-Number    |  |  |  |  |  |  |  |  |  |
|-------------|-------------|---|---|---|--|--|--|--|---|---|
| 125.073.027 | 156 040 130 | Cu  |   | 8 - 6   |  |  |  |  | a)  | 10  |

Technical Specifications: **Cone connecto FRL 4**

|                                |                      |
|--------------------------------|----------------------|
| Article No.                    | 125.073.027          |
| Wire diameter                  | 8 - 6 mm             |
| Suitable for solid cores       | Yes                  |
| Useful for stranded conductors | No                   |
| Nominal cross section          | 51 mm <sup>2</sup>   |
| Material                       | Cu                   |
| Sleeve form                    | Long                 |
| For pull protected connections | Yes                  |
| Suitable for round conductors  | Yes                  |
| Voltage level                  | Up to 35kV           |
| Model                          | Standard version     |
| Number of branches             | 2                    |
| Surface protection             | blank                |
| Oil stop/centre bar            | No                   |
| Type of connection             | Percussion connector |
| comment                        | a)                   |
| Commercial specification       |                      |
| Customs number                 | 85389000             |
| country of origin              | CH                   |
| Texte                          |                      |
| comment                        | a)                   |
| Logistic specification         |                      |
| VPE Weight                     | 2.12 kg              |

