


Conductor connections and junctions

■ AV 71 Connection for sheet metal with rivets



Application

For the following material thicknesses:
Inox, TiZn, Cu and AL up to 2.1 mm

Characteristics

Connection set for sheet metal ≥ 0.5 mm, including 7 rivets for lightening current carrying connection. Set can be also assembled on PVC coated surfaces.
Conductor connection with crimping wire lug
New: Riveting with hand pliers possible
New: Higher pull-out forces (H-Test)
New: The tightness is tested and guaranteed
New: The tightness compared to the old rivets has been improved (better surface pressure)
New: Tightness and H- certification guaranteed even after aging

Legend

a) Cable lug made of tinned copper

Article-Nr.	E-Number									
275.054.000	156 833 320	H	Cu	10	6	25				20

Accessories



Multi-range blind rivets AV 81

Article-Nr.	E-Number									
275.063.011	156 990 020	H	0.5 - 6.5	10	RAL 9006, silver	4.1			a)	70
275.063.012	156 990 030	H	0.5 - 6.5	10	RAL 8014, brown	4.1			b)	70

Technical Specifications: **Connection for sheet metal with rivets AV 71**

Article No.	275.054.000
Approved class H / N (EN 62561-1)	H
Material	Cu
KZ size of insert for crimp tool	10
Wire diameter	6 mm
Nominal cross section conductor	25 mm ²
Surface protection	unbehandelt
Type of connector	Access-clip
Commercial specification	
Customs number	85389000
country of origin	CH
Logistic specification	
VPE Weight	1.241 kg

