





## Foundation earthing components

### ■ FE 27 Connection part





**Characteristics**  
Without accessories.

Article-Nr.	E-Number	kA/s (S)		mm a						
281.076.000	156 940 970	6	InoxA4	180	M10					10
281.076.001	156 940 990	6	InoxA4	250	M10					25

#### Accessories







Mounting holder for connection sets 260.038.000

Article-Nr.	E-Number									
260.038.000	156 941 900	PVC								10

#### Accessories







Extension for connection 281.089.302

Article-Nr.	E-Number	H	kA/s (S)			mm a				
281.089.302	156 940 290	H	6	ok	InoxA4	285	M10			25

#### Accessories



Gasket for connection set 260.078.022

Article-Nr.	E-Number	H	kA/s (S)				mm D			
260.078.022	156 941 290	H	6	ok	InoxA4	M10	280			1

Technical Specifications: **Connection part FE 27**

	281.076.000	281.076.001
<b>Short circuit current</b>	6 kA/1s	
<b>Material</b>	InoxA4	
<b>Length a</b>	180 mm	250 mm
<b>Bolt dimension metric</b>	10	
<b>Internal thread</b>	M10	
<b>Connecting shaft</b>	10 mm	
<b>Diameter connection plate</b>	50 mm	
<b>Material connection lug</b>	rostfreier Stahl (V4A)	
<b>Commercial specification</b>		
<b>Customs number</b>	85389000	
<b>country of origin</b>	CH	
<b>Logistic specification</b>		
<b>VPE Weight</b>	2.1 kg	5.96 kg

