

## Connector CuZnNi

### ■ FRL 3 Connector











#### Material

Hexagon socket screws interior made of galvanised steel

#### Legend

- a) Drill eccentric
- b) Drill centric

| Article-Nr. | E-Number    |  |  |  |  |  |  |  |  |  |
|-------------|-------------|---|---|---|---|---|---|--|---|---|
| 123.125.106 | 156 000 135 | CuZnNi  | 12  | 150   | 17.2  | 28  | 85  |  | b)  | 10  |

Technical Specifications: **Connector FRL 3**

|                                  |                           |
|----------------------------------|---------------------------|
| Article No.                      | 123.125.106               |
| Material                         | CuZnvNi                   |
| Number of screws                 | 12                        |
| Nominal cross section conductor  | 150 mm <sup>2</sup>       |
| Eyelet diameter                  | 17.2 mm                   |
| External diameter                | 28 mm                     |
| Length a                         | 85 mm                     |
| Material conductor               | Kupfer                    |
| Insulation                       | No                        |
| Nominal cross section copper, RM | 120 - 150 mm <sup>2</sup> |
| Surface protection               | Other                     |
| Nominal cross section copper, RE | 120 - 150 mm <sup>2</sup> |
| Oil stop/centre bar              | No                        |
| required torque                  | 12 N·m                    |
| <b>comment</b>                   | b)                        |
| Commercial specification         |                           |
| Customs number                   | 85389000                  |
| country of origin                | CH                        |
| Texte                            |                           |
| <b>comment</b>                   | b)                        |
| Logistic specification           |                           |
| VPE Weight                       | 2.77 kg                   |

