








## Conductor connections and junctions

### ■ AV 11 Reducer DIN



#### Characteristics

For hexagonal pressing

Article-Nr.	E-Number									
414.065.259	156 071 120	H	Cu	10 - 12	6 - 8	25 - 35				25
414.065.269	156 071 230		Cu	12 - 14	8 - 10	35 - 50				10

## Technical Specifications: Reducer DIN AV 11

	414.065.259	414.065.269
Approved class H / N (EN 62561-1)	H	
Material	Cu	
KZ size of insert for crimp tool	10 - 12	12 - 14
Wire diameter	6 - 8 mm	8 - 10 mm
Nominal cross section conductor	25 - 35 mm <sup>2</sup>	35 - 50 mm <sup>2</sup>
Oil stop/centre bar	Yes	No
For pull protected connections	No	
Sleeve form	Short	
Suitable for round conductors	Yes	
Model	DIN-version	
Suitable for solid cores	Yes	
Number of branches	2	
Surface protection	blank	
Type of connection	Percussion connector	
Useful for stranded conductors	Yes	
Nominal cross section	35 mm <sup>2</sup>	50 mm <sup>2</sup>
Commercial specification		
Customs number	85389000	
country of origin	CE*	
Logistic specification		
VPE Weight	1 kg	0.58 kg

