

## Straight mechanical cable lug

### ■ PA 73 Straight mechanical cable lug










#### Characteristics

Straight mechanical cable lug for wire.  
Not suitable for lightning protection zone."

#### Legend

- a) wrench size 17
- b) wrench size 20

Article-Nr.	E-Number									
263.053.006	156 310 070	CuZnNi	6	53	22	9			a)	25
263.053.008	156 310 090	CuZnNi	8	55	25	11			b)	25

Technical Specifications: **Straight mechanical cable lug PA 73**

	263.053.006	263.053.008
<b>Length a</b>	53 mm	55 mm
<b>Height c</b>	22 mm	25 mm
<b>Wire diameter</b>	6 mm	8 mm
<b>Nominal cross section copper, RE</b>	28 mm <sup>2</sup>	50 mm <sup>2</sup>
<b>Nominal cross section copper, RM</b>	28 mm <sup>2</sup>	50 mm <sup>2</sup>
<b>Eyelet diameter</b>	9 mm	11 mm
<b>Material</b>	CuZnvNi	
<b>Bolt dimension metric</b>	8	
<b>Surface protection</b>	Other	
<b>Material conductor</b>	Kupfer	
<b>Commercial specification</b>		
<b>Customs number</b>	85389000	
<b>country of origin</b>	CE*	
<b>Logistic specification</b>		
<b>VPE Weight</b>	1.175 kg	1.535 kg

