

## T-screw connector

### ■ PA 70 T-screw connector



#### Characteristics







T" screw connector for wire.

Not suitable for lightning protection zone."

#### Legend

a) wrench size 17

b) wrench size 20

Article-Nr.	E-Number									
263.050.006	156 000 090	CuZnvNi	6	55	38				a)	25
263.050.008	156 000 130	CuZnvNi	8	58	40				b)	25

Technical Specifications: **T-screw connector PA 70**

	263.050.006	263.050.008
<b>Length a</b>	55 mm	58 mm
<b>Width b</b>	38 mm	40 mm
<b>Wire diameter</b>	6 mm	8 mm
<b>Nominal cross section copper, RE</b>	28 mm <sup>2</sup>	50 mm <sup>2</sup>
<b>Nominal cross section copper, RM</b>	28 mm <sup>2</sup>	50 mm <sup>2</sup>
<b>Material</b>	CuZnvNi	
<b>Surface protection</b>	Other	
<b>Voltage level</b>	Up to 30 kV	
<b>Material conductor</b>	Kupfer	
Commercial specification		
<b>Customs number</b>	85389000	
<b>country of origin</b>	CE*	
Logistic specification		
<b>VPE Weight</b>	1.887 kg	2.92 kg

