

## Earthing bars

■ **TES1570S** Telescopic earthing bar**Application**

Earthing for overhead contact lines

**Characteristics**

1 telescopic rod 4-parts, length adjustable from min. 1325 mm up to max. 4385 mm

1 earthing device consisting of:

- 1 Y-cable Cu 50 mm<sup>2</sup>, L = 6500 mm, transparent, isolated
- 1 contact wire hook resistant against throwing off, earthing connection bolt M12
- 2 short cut protected earthing clamps adjustable to all railheads

**Material**

Rod of polyester reinforced glass fibre, contact wire hook with CuNiSi

**Legend**

- 1) With signal flag
- 2) Without signal flag
- 3) Without bag

Article-Nr.	kA   ms I <sub>k</sub>								Kg	
645.120.000	40/100								12.9	2

**Accessories**

Earthing device 649.001.010

Article-Nr.									Kg
649.001.010	40 - 120								9.2

**Accessories**

Earthing device 649.001.030

Article-Nr.									Kg
649.001.030	40 - 120								10.4

**Accessories**

Earthing device 649.001.031

Article-Nr.									Kg
649.001.031	35 - 120								8

**Accessories**

Signal flag with clip on 649.001.008

Article-Nr.	mm								Kg	
649.001.008	44								0.4	1



## Accessories



Signal flag 640.055.000

Article-Nr.									
640.055.000	44								2

## Accessories



Signalflag without fixing 649.002.000

Article-Nr.									
649.002.000	44								3

## Accessories



Bag 649.001.131

Article-Nr.									
649.001.131									0.5

Technical Specifications: **Telescopic earthing bar TES1570S**

Article No.	645.120.000
<b>Short circuit current</b>	40/100
<b>comment</b>	2
Commercial specification	
<b>Customs number</b>	85359000
<b>country of origin</b>	undefined
Texte	
<b>comment</b>	2
Logistic specification	
<b>Kilo / piece</b>	12.9 kg

